


APOLLO EXPORT



PRIMJENA

MATERIJAL CIJEVI:
OJAČANJE:
TEMPERATURA:

usis i tlak vode i fekalija -
otporna je na atmosferske utjecaje i niske temperature
mješavina NBR gume i PVC-a sive boje
spirala od tvrdog PVC-a plave boje
-25 +60 °C



Promjer (mm)	Tlak (bar)	Podtlak (bar)	Težina (kg/m)	Pol. sav. (mm)	Kolut (m)	Montaža	
						Obujmice	
50	5.0	0.9	1.050	200	50	22 60 - 63 Fe/Zn	BAND - IT
60	4.5	0.9	1.250	240	50	24 68 - 73 Fe/Zn	
63	4.5	0.9	1.390	240	50	24 74 - 79 Fe/Zn	
76	4.0	0.9	1.700	300	50	24 86 - 91 Fe/Zn	
80	3.5	0.9	1.850	320	30	24 92 - 97 Fe/Zn	
90	3.5	0.9	2.250	360	30	24 98 - 103 Fe/Zn	
102	3.0	0.9	2.700	400	30	24 113 - 121 Fe/Zn	
110	3.0	0.9	3.100	440	20	24 122 - 130 Fe/Zn	
120	2.5	0.9	3.600	480	20	26 131 - 139 Fe/Zn	
127	2.5	0.9	3.900	510	20	26 140 - 148 Fe/Zn	
152	2.0	0.9	5.000	610	20	26 162 - 174 Fe/Zn	
203	1.5	0.9	10.000	800	20	26 214 - 226 Fe/Zn	

Napomena:

Premala širina utora na nogicama Storz priključaka u odnosu na širinu obujmica onemogućava da se oni pomoću njih montiraju na ove cijevi unutarnjeg promjera manjeg od 75 mm