



# EOLO PU



## PRIMJENA

usis i prolaz šećera, brašna, žitarica i druge hrane - zbog glatke unutarnje površine i velike otpornosti na habanje koriste se i za usis piljevine i otpiljaka

## MATERIJAL CIJEVI:

atoksični prozirni PU

## OJAČANJE:

spirala od tvrdog PVC-a žute boje

## TEMPERATURA:

-25 +85 °C

Promjer (mm)	Deblj. stijenke (mm)	Podtlak (bar)	Tezina (kg/m)	Pol. sav. (mm)	Kolut (m)	Montaža	
						Obujmice	
20	0.40 – 2.50	0.25	0.100	25	20	18	23 - 25 Inox
25	0.40 – 2.60	0.25	0.140	30	20	20	29 - 31 Inox
30	0.40 – 2.50	0.25	0.140	35	20	20	32 - 35 Inox
32	0.40 – 2.60	0.20	0.155	35	20	20	36 - 39 Inox
35	0.50 – 2.70	0.20	0.170	45	20	20	40 - 43 Inox
38	0.50 – 2.90	0.20	0.195	50	20	22	44 - 47 Inox
40	0.50 – 3.00	0.20	0.200	60	20	22	44 - 47 Inox
45	0.50 – 3.20	0.20	0.245	65	20	22	52 - 55 Inox
50	0.50 – 3.30	0.20	0.290	70	20	22	56 - 59 Inox
55	0.50 – 3.30	0.20	0.360	75	20	23	68 - 73 Inox
60	0.50 – 3.50	0.16	0.425	80	20	23	68 - 73 Inox
63	0.50 – 3.50	0.16	0.460	80	20	23	68 - 73 Inox
70	0.50 – 3.80	0.16	0.500	95	30	23	74 - 79 Inox
76	0.50 – 3.80	0.16	0.550	100	30	23	80 - 85 Inox
80	0.50 – 4.20	0.16	0.590	110	30	23	86 - 91 Inox
90	0.60 – 4.40	0.14	0.670	125	30	23	98 - 103 Inox
100	0.60 – 4.40	0.13	0.750	140	30	23	104 - 112 Inox
110	0.60 – 5.20	0.12	0.900	150	30	23	113 - 121 Inox
120	0.60 – 5.20	0.10	1.000	160	30	23	122 - 130 Inox
127	0.60 – 5.20	0.10	1.100	170	30	23	131 - 139 Inox
130	0.60 – 5.20	0.09	1.200	170	20	23	140 - 148 Inox
140	0.70 – 5.30	0.09	1.300	180	20	23	149 - 161 Inox
150	0.70 – 5.60	0.08	1.500	200	20	23	149 - 161 Inox
160	0.80 – 6.20	0.07	1.780	220	20	23	162 - 174 Inox
170	0.80 – 6.20	0.05	1.900	230	20	26	175 - 187 Inox
180	0.80 – 6.70	0.04	2.000	250	20	26	188 - 200 Inox
200	0.80 – 6.60	0.04	2.200	260	20	26	201 - 213 Inox
250	0.80 – 6.70	0.04	3.300	300	10		
300	0.80 – 7.00	0.03	4.000	350	10		

BAND - IT