

PLUTONE PO



PRIMJENA

MATERIJAL CIJEVI:

OJAČANJE:

TEMPERATURA:

usis i tlak nafte, naftnih derivata i hidrauličnog ulja
glatka termoplastična (PVC/NBR) guma crne boje
poliesterska mreža, čelična spirala i bakrena pletenica
-30 +80 °C

Promjer (mm)	Radni tlak (bar)	Rasprs. tlak (bar)	Podtlak (bar)	Težina (kg/m)	Pol. sav. (mm)	Kolut (m)	Montaža	
							Obujmice	
20 x 29	14	42	1.0	0.470	60	60	29 - 31 Inox	-
25 x 35	12	36	1.0	0.650	80	60	32 - 35 Inox	
32 x 43	11	33	0.9	0.880	100	60	40 - 43 Inox	
38 x 49	10	30	0.9	1.030	110	40	48 - 51 Inox	
40 x 51	10	30	0.9	1.070	120	40	48 - 51 Inox	
45 x 58	9	27	0.8	1.470	140	40	56 - 59 Inox	
50 x 63	8	24	0.8	1.620	150	40	60 - 63 Inox	BAND - IT
60 x 74	7	21	0.8	2.040	180	30	74 - 79 Inox	
63 x 77	7	21	0.8	2.130	190	30	74 - 79 Inox	
76 x 91	6	18	0.7	2.670	230	30	86 - 91 Inox	
80 x 95	5	15	0.7	2.770	240	30	92 - 97 Inox	
90 x 106	5	15	0.7	3.460	270	30	104 - 112 Inox	
102 x 118	4	12	0.7	3.800	310	20	102 - 118 Inox	